

CDR-915 • Spread Spectrum Data Transceiver



The CDR-915 is a low cost, high performance spread spectrum data radio transceiver. Its design allows easy integration into OEM applications and is FCC and Industry Canada approved.

Key Benefits

- Low cost
- Small footprint
- Easy integration (OEM Developer's kit available)
- Fast throughput (50kbps RF data rate)
- Transparent Protocol
- Powerful Windows™ based path management software tracks 16 radios simultaneously
- Full duplex emulation
- Standard interface
- Transparent or Guaranteed Point-to-Point or Point-to-Multi-Point data delivery modes
- Field upgradeable
- Programmable as a system repeater for extended range

Applications

- HVAC control
- Vending
- SCADA systems
- Wireless Network Nodes
- Security systems
- Industrial controls
- Field area networks
- Most any application currently using an RS-232 or RS-485 serial connection

Specifications

Frequency	902-928 MHz
Frequency Control	PLL Synthesizer
Transport	Transparent
	Point-to-Point
	Point-to-Multipoint
	Multipoint-to-Multipoint
	Broadcast and Guaranteed Delivery
Data Interface	Asynchronous TTL
Hopping Channels	25
Configuration	Windows™ Application
Addressing	65,025 Unique Addresses
Duty Cycle	100% Receive, 50% Transmit
Data Interface Rate	2400,4800,
	9600,19.2k,56k bps (N,8,1)
Temperature	-30 to +70 °C
Range*	up to 10 miles
Data Encoding	Proprietary Method
Receiver Sensitivity	-101 dBm usable
Modulation	Direct FM (FSK)
RF Data Rate	50 kbps
Data Flow Control	Hardware using CTS
Transmitter Output	200mW
Error Detection	16-bit CRC
Input Voltage	8 – 14 VDC
Input Current	70mA Receive Mode
	250mA Transmit Mode

Regulatory

United States (FCC)	CFR 15.247 Approved
Canada (IC)	RSS210 Approved

Mechanical

Size	1.75" x 2.925"
Antenna Connector	Reverse SMA

Interface Options

- RS-232/485 (p/n INT-232/485 Combo)
- MODBUS™ I/O Board
- USB (p/n INT-USB)

Developer's Kit

The CDR-915 OEM Design Kit includes a manual, software and two each of the following.

- CDR-915 Data Radio Transceiver
- INT-/485 Combo Interface Board
- ¼ Wave Antenna
- Power Supply Modules
- Serial Cables

Specifications are subject to change without notice. *The effective transmission range will vary based on antenna selection, installation location and other factors.